

# Dromex



## MAXI VIEW GOGGLES



DV-004MAX



### Description

Dromex® DV-004MAX goggles with indirect vent and polycarbonate mono lens is designed to protect the users' eyes from flying debris, particles, light chemical splashes and UV (Ultra Violet) light during work activities such as grinding. Suitable in engineering workshops, factories, warehouse and general industries.

Designed for compatibility with other PPE such as industrial hats, hearing protectors and respiratory half mask devices and as overspecs with prescription spectacles. The DV-004MAX goggle is easy to put on with gloves and is lightweight with an impact resistant, anti-scratch and anti-fog polycarbonate lens. These features ensure a firm fit promoting enhanced product performance and user comfort.

DV-004MAX features efficient indirect ventilation and a wide face contact area for comfort and seal that protects the eyes from high speed, low energy impact particles.

### Special Instructions

- Failure to adhere to all instructions and precautionary measures can result in injury.
- If the user has eye conditions or vision impairment, they must consult with a registered physician prior to use.
- Any damages to this protective device may reduce clarity of sight that could result in injury.
- Following any major detectable defects on the goggle, the goggle should be replaced immediately.
- This eye protector is suitable for use to the lowest marking on the lens (ocular) and frame.
- If the lens becomes damaged, the eye protector should be replaced.
- It shall be the responsibility of the persons and organizations that use this goggle to establish safety and health practices and to determine the applicability of regulatory limitations prior to use of this goggle.
- This goggle is designed to be used with other PPE equipment.

### Compliance & Conformity

Conforms to CE, EN 166:2001. Revision of certification in progress.

Quality System as per ISO 9001:2008.

### Specifications

Style:	Clear polycarbonate lens goggle with vents and wide adjustable head straps
Lens:	Polycarbonate clear UV filter, shade 2-1,2 with anti-fog and scratch resistant lens
Frame:	Polyvinyl chloride indirect vented frame and with a 25mm elastic head band
Refractive Power:	±0.06 D
Astigmatism:	0.06 D
Optical class:	1 - ± 0, 06 DIOPETRES for permanent wear
Lateral vision:	180 degrees
Minimum Velocity particles:	Class F, 45 m/s
Mass:	124g

### Packaging, Storage & Obsolescence

Individually wrapped goggles in a polybag, sold as 100 goggles per carton. Store in a cool dry place.



### Inspection Frequency and Details

Prior to use the goggle should be free of any potential contaminants that can affect its intended performance.

The goggle should be inspected by the user at the end of every use and then again prior to each use.

Cracked eyewear must be removed from service as they will reduce eye protection and obstruct vision.

### Cleaning & Maintenance

Designed as reusable protective eyewear. After use clean with a mild cleaning liquid, carefully rinse off all traces of the cleaning liquid and dry with a soft cloth and gently wipe with a soft spectacle cleaning material. Do not clean on clothing nor use abrasive cleaners.

### Limitations of Use

These goggles should not be used for any athletic game, recreational activities, paintball or simulated water activities. These goggles are not suitable to protect from chemical, biological, radiological, and nuclear (CBRN) agents.

### Recommendations and Restrictions

The use of this goggle is restricted to the scope and application as intended by EN 166:2001.

### Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Safety eyewear should be disposed of considering the hazardous substance they were used for or could be contaminated with. Please consider recycling.

### Materials



1. Clear polycarbonate lens.
2. Polycarbonate clear UV filter.
3. Polyvinyl chloride indirect vented frame.
4. Adjustable 25mm Elastic head band.

### Marking

